

## Accessories

To achieve the high performance requirements of our system solution, a range of superior quality accessories are available. This includes performance tapes, high-strength screws, and jointing compounds that achieve seamless joints.

### Access Panel

#### Product Characteristics


Vinh Tuong access panels are designed for use in concealed ceiling systems where there is a requirement to access services for maintenance purposes.

#### Applications

Used for concealed ceiling systems.

#### Product matrix

Product name	Panel size (mm)	Overall size (mm)	Thickness (mm)
Access Panel	450 x 450	603 x 603	9; 12.5
	600 x 600	800 x 800	9; 12.5



### VT Corner Bead

#### Product Characteristics

Perforated galvanised metal bead with 90° angle.

#### Applications

Used to reinforce external corner of drywall concealed ceiling, especially step ceiling systems

#### Product matrix

Product name	Sectional dimension W x H (mm)	Thickness (mm)	Length (mm)
VT Corner Bead	30 x 30	0.5	2700
	23 x 23		



## Accessories

### VT Wall Angle





#### Product Characteristics

VT Wall Angle is wall angle, used along the wall perimeter.

#### Applications

Used for in grid and concealed ceiling systems.

#### Product matrix

Product name	Sectional dimension W x H (mm)	Thickness (mm)	Length (mm)
VTC 18/22	18 x 22	0.4	3600
			
VT 18/22	18 x 22	0.4	3600
			
VT 15/20	15 x 20	0.4	3600
			
VT EliteLINE 18/18	18 x 18	0.34	3600
			

### VT Shadowline/ Z Wall Angle



#### Product Characteristics

This is special type wall angle, used to form sharp looking shadow-line effect, along ceiling perimeters.

#### Applications

Used in concealed ceiling systems.

#### Product matrix

Product name	Sectional dimension W x H (mm)	Thickness (mm)	Length (mm)
VT Shadowline	30 x 20	1	3000
			
Z Wall angle	12 x 15.8 x 23 12 x 12.7 x 23 12 x 9 x 23	0.5	2700
			

## Accessories

### VT Screw

#### Product Characteristics

It is high performance, corrosion resistant. The length of selected screw should be sufficient to give a nominal 10mm penetration into metal framing.



#### Applications

Used to fix plasterboard to metal frames, and metal to metal frames.

#### Manufacturing Standards

BS EN 14566:2008

#### Product matrix

Product name	Length (mm)	Quantity per Unit (kg/bag)
 VT Drywall Screw	25	1
	40	
	60	
 VT Wafer Head Screw	15	1

## Accessories

### Suspension components













#### Product Characteristics

Galvanized metal suspension components, including following items:

#### Product matrix

#### Applications

Used for ceiling systems.

Product name	W x H (mm)	Thickness (mm)	Quantity per Unit	Length (mm)	Diameter (mm)
<b>Spring Clip</b>					
Spring Clip PK223	40 x 12	0.79	600 pcs/box	140	
					
Hanger Clip OMEGA	40 x 23	0.79	1000 pcs/box	80	
					
<b>Clip</b>					
ALPHA Clip	25 x 48	0.5	2500 pcs/box		
					
OMEGA Clip	42 x 15	0.8	400 pcs/box	80	
					
TRIFLEX Clip	50 x 50	0.8	1000 pcs/box		
					
<b>Suspension Rod</b>			50 pcs	2700	3; 4 6; 8; 10
					
<b>Hanging Rod</b>			50 pcs	330	3; 4
					
<b>Rod Joiner</b>			2000 pcs/box		4.6
					
<b>Soffit Cleat</b>			2500 pcs/box		6; 8
					
<b>Expansion Bolt</b>			1 pcs/box	43	6; 8
					
<b>Suspension Bolt</b>			100 pcs/box 50 pcs/box (10mm)	40	6; 8; 10
					
<b>Nut</b>			500 pcs/box		6; 8; 10
					

## Accessories

### VT Paper Tape

#### Product Characteristics

VT Paper Tape is used for jointing treatment in concealed ceiling and drywall systems. Having high breaking strength, it is free from cracking.

#### Applications

For jointing plasterboard in wall, lining and concealed ceiling system.

#### Manufacturing Standards

EN 13963:2014

#### Product matrix

Product name	Width (mm)	Length (m)
VT Paper Tape	50	75



### VT Glass Fiber Mesh Tape

#### Product Characteristics

VT Glass Fiber Mesh Tape, with self-adhesion on the surface of the plasterboard, is used for jointing treatment in concealed ceiling systems.

#### Applications

For jointing plaster board in concealed ceiling system.

#### Manufacturing Standards

EN 13963:2014

#### Product matrix

Product name	Width (mm)	Length (m)
VT Glass Fiber Mesh Tape	50	90



## Accessories

### Gyp-Filler Jointing Compound

#### Product Characteristics

Gyp-Filler is a special gypsum powder mixed with other active ingredients. The special formula provides high level of adhesion to the plasterboard surface and high flexural strength, prevent from cracking.

#### Applications

For plasterboard jointing treatment in Gyproc drywall and ceiling systems.

#### Manufacturing Standards

EN 13963:2014

#### Quantity per Unit

20kg/bag

